
WULKAN 200

for all types of wheels for passenger cars and vans with any type of rims and tyres

General features:

- triple acoustic insulation system (rubber lining, perforated PVC shield, foam)
- anti-vibration rubber feet
- possible adjusting of washing and drying times in the production stagee
- counter of starts display option available
- new design on request

Standard equipment:

- WULKAN MIX granulate - 25 kg
- granulate basket
- WULKAN TURBO washing concentrate - 20 l

| | |
|---|---------------------|
| Wheel diameter range | 560 - 800 mm |
| Wheel width range | 135 - 305 mm |
| Maximum weight of wheel | 60 kg |
| Washing times, factory set (adjustable, 3 programmes)* | 20, 40, 60 sec |
| Drying time, factory set (adjustable, 1 programme)** | 15 sec |
| Pump drive 3-phase 400 V, 50 Hz, 5.5 kW | 2900 rpm |
| Pump efficiency | 600 lpm |
| Wheel drive 3-phase 400 V, 50 Hz, 0.37 kW | 930 rpm |
| Motors and drive power | 6 kW |
| Water pressure | 4 bar |
| Quantity of water | 150 l |
| Quantity of WULKAN MIX granulate | 17.5 kg |
| Quantity of WULKAN TURBO washing concentrate | 1.5 l |
| Compressed air working pressure | 8 - 12 bar |
| Sound level at 1 m distance | 77.0 dB(A) |
| Acoustic power level | 88.6 dB(A) |
| Dimensions (width x depth x height) | 900 x 910 x 1355 mm |
| Net weight | 270 kg |
| Maximum limiting number of washing process starts (service lock) | 200 starts |

*/**adjustable only in the production stage