
WULKAN 300H

for all types of wheels for passenger cars and vans with any type of rims and tyres, with water heating system

General features:

- computer control
- software in 5 languages
- user-friendly display
- sedimentation tank separated from washing chamber
- triple acoustic insulation system (rubber lining, perforated PVC shield, foam)
- anti-vibration rubber feet
- available in 3 x 230 V power supply option
- new design on request

Heating system:

- heater power - 4 kW
- water heating time to 50°C: 60 - 120 min
- overheating protection

Standard equipment:

- WULKAN MIX granulate - 25 kg
- granulate basket
- WULKAN TURBO washing concentrate - 30 l

Wheel diameter range	560 - 800 mm
Wheel width range	135 - 305 mm
Maximum weight of wheel	60 kg
Washing times, factory set (adjustable, 3 programmes)	20, 40, 60 sec
Drying time, factory set (adjustable, 1 programme)	15 sec
Water heating time to 50°C	60 - 120 min
Heater power	4 kW
Pump drive 3-phase 400 V, 50 Hz, 5.5 kW	2900 rpm
Pump efficiency	600 lpm
Wheel drive 3-phase 400 V, 50 Hz, 0.37 kW	930 rpm
Motors and drive power	6 kW
Water pressure	4 bar
Quantity of water	300 l
Quantity of WULKAN MIX granulate	20 kg
Quantity of WULKAN TURBO washing concentrate	3 l
Compressed air working pressure	8 - 12 bar
Sound level at 1 m distance	77.2 dB(A)
Acoustic power level	87.1 dB(A)
Dimensions (width x depth x height)	900 x 1212 x 1450 mm
Net weight	310 kg
Maximum limiting number of washing process starts (service lock)	500 starts

*/**adjustable only in the production stage