

---

# WULKAN 360HP

for all types of wheels for passenger cars, vans, off-road vehicles and SUVs with the width of up to 360 mm with any type of rims and tyres, with water heating system and pneumatic wheel stabilisation system

## General features:

- computer control
- software in 5 languages
- user-friendly display
- servomotor with an arm keeping narrower wheels in vertical position
- sedimentation tank separated from washing chamber
- triple acoustic insulation system (rubber lining, perforated PVC shield, foam)
- anti-vibration rubber feet
- new, attractive design
- available in 3 x 230 V power supply option

## Heating system:

- heater power - 4 kW
- water heating time (to 50°C): 60 - 120 min
- overheating protection

## Standard equipment:

- WULKAN MIX granulate - 25 kg
- granulate basket
- WULKAN TURBO washing concentrate - 30 l
- plastic protective cover
- rubber anti slip mat

<b>Wheel diameter range</b>	560 - 800 mm
<b>Wheel width range</b>	135 - 360 mm
<b>Maximum weight of wheel</b>	60 kg
<b>Washing times, factory set (adjustable, 3 programmes)</b>	20, 40, 60 sec
<b>Drying time, factory set (adjustable, 1 programme)</b>	15 sec
<b>Water heating time to 50°C</b>	60 - 120 min
<b>Heater power</b>	4 kW
<b>Pump drive 3-phase 400 V, 50 Hz, 5.5 kW</b>	2900 rpm
<b>Pump efficiency</b>	600 lpm
<b>Wheel drive 3-phase 400 V, 50 Hz, 0.37 kW</b>	930 rpm
<b>Motors and drive power</b>	6 kW
<b>Water pressure</b>	4 bar
<b>Quantity of water</b>	300 l
<b>Quantity of WULKAN MIX granulate</b>	20 kg
<b>Quantity of WULKAN TURBO washing concentrate</b>	3 l
<b>Compressed air working pressure</b>	8 - 12 bar

---

<b>Sound level at 1 m distance</b>	77.2 dB(A)
<b>Acoustic power level</b>	87.1 dB(A)
<b>Dimensions (width x depth x height)</b>	960 x 1212 x 1450 mm
<b>Net weight</b>	330 kg
<b>Maximum limiting number of washing process starts (service lock)</b>	500 starts

\*/\*\*adjustable only in the production stage